### (12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

## (19) World Intellectual Property Organization International Bureau



# 

(43) International Publication Date 9 September 2005 (09.09.2005)

## **PCT**

# (10) International Publication Number WO 2005/083865 A1

(51), International Patent Classification7: H01M 10/44

H02J 7/00,

English

(21) International Application Number:

PCT/JP2005/003827

1 March 2005 (01.03.2005) (22) International Filing Date:

(25) Filing Language:

(26) Publication Language: English

(30) Priority Data: 2004-056056

1 March 2004 (01.03.2004) JP

- (71) Applicant (for all designated States except US): RICOH COMPANY, LTD. [JP/JP]; 3-6, Nakamagome 1-chome, Ohta-ku, Tokyo, 1438555 (JP).
- (72) Inventor; and
- (75) Inventor/Applicant (for US only): NISHIDA, Junji [JP/JP]; 10-3, Midorimachi, Neyagawa-shi, Osaka, 5720022 (JP).
- (74) Agent: ITOH, Tadahiko; 32nd Floor, Yebisu Garden Place Tower, 20-3, Ebisu 4-chome, Shibuya-ku, Tokyo, 1506032 (JP).


- (81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SM, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.
- (84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IS, IT, LT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

#### Published:

with international search report

[Continued on next page]

(54) Title: BATTERY CONNECTION DETECTION CIRCUIT



(57) Abstract: A battery connection detection circuit is disclosed that is able to correctly determine an operation condition of a secondary battery and a connection condition between the secondary battery and a charging device. A determination circuit monitors both the voltage Vt1 on the battery connection terminal T1 and the current supplied to the secondary battery BAT, and therefore, the determination circuit can correctly determine the operation condition of the secondary battery and the connection condition between the secondary battery and the charging device even when high frequency noise is superposed on the power supply voltage Vdd, and when the power supply voltage decreases.



For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.